# MIDI SIDE VIEW 13X12MM LED NEON FLEX, RGBW **COLOUR CHANGING, 24V, IP67 (10M KIT)**

**I SKU: NEONSIDE1312/10MKIT-RGBW** 


























## **Neon Specifications**

SKU Code	NEONSIDE1312/10MKIT-RGBW
Voltage	24V
Watts p/M	16W p/M
Colour Temp	Red: 620-630nm
	Green: 525-530nm
	Blue: 465-470nm
	White: 5000K   620 lm p/m
Min Bend Radius	60mm
CRI	90
Dimensions	13mm x 12mm x 10000mm
IP Rating	IP67
IK Rating	IK08
Cut Points	Every 62.5mm
Operating Temp	-20°C to +45°C
Lifespan	Up to 36000 Hours
Certification	CE, RoHs, UL, Reach
Guarantee	3 Years

## **Driver Requirements**

1 Metre	> 17W
2 Metres	> 34W
3 Metres	> 51W
4 Metres	> 68W
5 Metres	> 85W
6 Metres	> 102W
7 Metres	> 119W
8 Metres	> 136W
9 Metres	> 153W
10 Metres	> 170W







ultraleds.co.uk



0800 088 3300



✓ orders@ultraleds.co.uk

# **FEATURES & BENEFITS**

- Featuring a 90 CRI spot free high lumen output, this revolutionary neon flex can be recessed or surface mounted making it a complete, highly versatile systematic installation solution
- High quality, high brightness
- Suitable for indoor and outdoor use
- Salt Water Resistant Solvent Resistant **UV** Resistant Flame Resistant

# **DESCRIPTION**

Introducing our IP67 Silicone Neon Flex, at only  $13 \times 12$ mm and featuring a 90 CRI spot free high lumen output, this revolutionary neon flex can be recessed or surface mounted making it a complete, highly versatile systematic installation solution.

Also featuring resistance to saline solutions, acid & alkali, corrosive gases, fire and UV, this Neon Flex is a perfect lighting solution for both heavy duty and display lighting requirements. These features make this Neon Flex suitable for installations on yatchs, super yatchs, facade lighting, indoor and outdoor projects.

Making use of a vertical bend and side light emittance it can be easily moulded and shaped to your requirements and is a more up to date modern solution to PVC neon.

#### This 10 metre kit includes

A 10 metre reel of silicone neon flex with a 45cm 5 Core tinned end power cable at each end, 1 set of end caps, 1 silicone glue tube,  $1 \times 5$  Core tinned end connector cable 28 PC mounting clips. The cable length can be extended at each end to your specification. Please get in touch if you would like a quote for this service.

#### **GALLERY**





