## 2.4GHz wireless transmitting 4-zone individually control

Easy installation, safe and reliable

Mi · Light <sup>®</sup>		2.46 R	r.D
•Light <sup>®</sup>	2.46 RF	a	
			III.
		II Spec	NG+
te Mode	Speed Speed	0	ī
		n l	4
1 2 0 0	3 4	-	

SKU code	U4ZONET3	
Voltage	180~240V	
Transmission Type	RF 2.4GHz	
Transmission Frequency	2400-2483.5MHz	
Transmitting Power	6dBm	
Modulation Method	GFSK	
Control Distance	30 Metres (without obstructions)	
Diming Range	1~100%	
Panel Type	Glass - Scratch Resistant	
Panel Size	86mm x 86mm	
Panel Depth	33mm	
Colour	RGB & RGB with White	
IP Rating	IP20	
Operating Temperature	-20°C ~ +60°C	
Certification	CE-EMC CE-LVD ROHS	
Warranty	3 years	

## Wall Mounted Glass Panel Remote Control, RGB & White

The wall mounted glass panel series of controllers are premium alternatives to handheld remotes. These panels fit standard socket back boxes and are very easy to install.

Features include a delay button, which will fade out the lights after 60 seconds. Handy when you only need them on momentarily.

4 Zones - You can connect endless receivers to 4 different zones in your home, for example your kitchen could have 10 lights, your bathroom 4 lights etc.

Easy to use touch screen with scratch resistant tempered glass. Fade from 100% down to 1% and switch all zones off with a single button.