

# CIRCULAR LED NEON FLEX, GREEN, 24V, IP65 (SOLD PER METRE)

| SKU: TL-NEONCIRC24-GRE



ULTRA LEDES

[ultraleds.co.uk](https://ultraleds.co.uk)

0800 088 3300

[orders@ultraleds.co.uk](mailto:orders@ultraleds.co.uk)



## FEATURES & BENEFITS

Our Circular Display Neon Flex offers full illumination in an 18mm diameter, making it perfect for single use display lighting both indoors and outdoors.

High quality, high brightness

Suitable for indoor and outdoor use

Salt Water Resistant  
Solvent Resistant  
UV Resistant  
Flame Resistant





## TECHNICAL INFORMATION

### Neon Specifications

SKU Code	TL-NEONCIRC24-GRE
Voltage	24V
Watts p/M	8.4W p/M
Colour Temp	Green: 520-530nm
Lumens p/M	641LM
LED Chip Type	SMD 2835
Max Bend Radius	80mm
CRI	80
Dimensions	18mm x 18mm x 1000mm
IP Rating	IP65
IK Rating	IK08
Cut Points	Every 4.2cm
Operating Temp	-20°C to +45°C
Lifespan	Up to 50000 Hours
Certification	CE, RoHs, UL, Reach
Guarantee	1 Years

### Driver Requirements

1 Metre	> 9W
2 Metres	> 17W
3 Metres	> 26W
4 Metres	> 34W
5 Metres	> 42W
6 Metres	> 50W
7 Metres	> 60W
8 Metres	> 70W
9 Metres	> 80W



## DESCRIPTION

Our Circular Display Neon Flex offers flexible illumination in an 18mm diameter, making it perfect for single use display lighting both indoors and outdoors.

Fully diffused PVC ensures “no shadow”, no spotting illumination for a durable, high quality lighting display.

Neon flex can be used in some instances to replicate traditional neon where fragile glass isn't suitable. Neon Flex looks better than glass neon - and it opens all the environments where fragile Glass Neon cannot be used. As the name suggests, it is highly flexible. LED Neon Flex can be bent to a minimum radius of 8 cm, and can be cut easily to your desired lengths with the use of 4.17cm cut points. Maximum Length at any time is 9 metres.

**For a working Neon Flex installation you will need:**

- Neon Flex LED
- 1 x Neon Flex Power Cable
- 1 x Neon Flex Connector Pin
- 1 x Neon Flex End Cap
- 1 x 24V Power Supply

---

## GALLERY

