CIRCULAR LED NEON FLEX, RED, 24V, IP65 (SOLD PER METRE)
| SKU: TL-NEONCIRC24-RED

IP65 | **RED** | **24V** | **Dimmable** | **80 CRI** | **CE EMC** | **CE LVD** | **RoHs** | **1YR Guarantee**

FEATURES & BENEFITS

Our Circular Display Neon Flex offers flexible illumination in an 18mm diameter, making it perfect for single use display lighting both indoors and outdoors.

High quality, high brightness

Suitable for indoor and outdoor use

Salt Water Resistant
Solvent Resistant
UV Resistant
Flame Resistant

TECHNICAL INFORMATION

Neon Specifications

SKU Code	TL-NEONCIRC24-RED
Voltage	24V
Watts p/M	7.8W p/M
Colour Temp	Red: 620-630nm
Lumens p/M	265LM
LED Chip Type	SMD 2835
Max Bend Radius	80mm
CRI	80
Dimensions	18mm x 18mm x 1000mm
IP Rating	IP65
IK Rating	IK08
Cut Points	Every 4.2cm
Operating Temp	-20°C to +45°C
Lifespan	Up to 50000 Hours
Certification	CE, RoHs, UL, Reach
Guarantee	1 Years

Driver Requirements

1 Metre	> 9W
2 Metres	> 17W
3 Metres	> 26W
4 Metres	> 34W
5 Metres	> 42W
6 Metres	> 50W
7 Metres	> 60W
8 Metres	> 70W
9 Metres	> 80W

R > 80mm

18mm

18mm

DESCRIPTION

Our Circular Display Neon Flex offers flexible illumination in an 18mm diameter, making it perfect for single use display lighting both indoors and outdoors.

Neon flex can be used in some instances to replicate traditional neon where fragile glass isn't suitable. Neon Flex looks better than glass neon - and it opens all the environments where fragile Glass Neon cannot be used. As the name suggests, it is highly flexible. LED Neon Flex can be bent to a minimum radius of 8 cm, and can be cut easily to your desired lengths with the use of 4.17cm cut points. Maximum Length at any time is 9 metres.

For a working Neon Flex installation you will need:

- Neon Flex LED
- 1 x Neon Flex Power Cable
- 1 x Neon Flex Connector Pin
- 1 x Neon Flex End Cap
- 1 x 24V Power Supply

GALLERY