

12V TAGRA® PROFESSIONAL THIN LED DRIVER, IP20, 45W

| SKU: TAGTHIN12V45W



12V

IP20



WHITE

SELV



TECHNICAL INFORMATION

Specifications

Output	Start Up Time	< 0.5 secs
	Output Voltage	12V +/- 5%
	Output Current	0 - 3.75A
	Output Voltage Wave	180mV
	Output Overload	Yes
Input	Input Voltage	AC220-240V
	Input Frequency	50/60Hz
	Input Current	< 0.3A
	Input Power	< 60W
	Efficiency	> 85%
	Standby	< 0.5W
	Inrush Current	< 60A
Environment	Power Factor	> 0.9
	Operating Temp.	-20°C~45°C
	Relative Humidity	45%~85% RH
	Max. Case Temp.	80°C
	Lifetime	30,000 Hours
	Working Noise	Yes



ULTRA LEDs



ultraleds.co.uk



0800 088 3300




orders@ultraleds.co.uk

FEATURES & BENEFITS

- High Cost Performance
- SELV
- Open Circuit Protection
- Short Circuit Protection
- Overload Protection
- Over Temperature Protection
- Compliance to ERP directive
- Slim linear design
- Lifetime 30,000 Hours

Mechanical	Case Material	Plastic
	Mounting	Independent
	Insulation Type	Class II
	IP Rating	IP20
	Input Cables	Terminal Block
	Output Cables	Terminal Block
	Output Cables Length	- -
Protection	Open Circuit	- -
	Overload	Yes
	Short Circuit	Yes
	Over Temperature	Yes
	Over Voltage	Yes
	Auto Recovery	Yes
	Latch Off	Yes
Safety & EMC	Safety	IEC61347-1 IEC61347-2-13
	Harmonic	EN61000-3-2
	EMI	EN55015
	EMS	EN61547



DIMENSIONS